

# KRYPTON

## PRODUCT SPECIFICATION

DESCRIPTION	STANDARD USED	SPECIFICATION
MANUFACTURING METHOD	-	TUFTED
MACHINE GAUGE	INCHES	1/10
PILE CONSTRUCTION	-	LOOP PILE
PILE YARN COMPOSITION	-	100% SOLUTION DYED NYLON
PRIMARY BACKING	GM./M2	90 NON WOVEN
SECONDARY BACKING	GM./M2	750 LATEX PRE COAT
BITUMEN PLUS NON WOVEN FLEECE	GM./M2	2,500
PILE WEIGHT	GM./M2	500
TOTAL WEIGHT	GM./M2	3,840
PILE HEIGHT	MM	3.50
STITCH RATE	ST PER 10CM	43.5
STITCH DENSITY	TUFTS/M2	171,260
PRODUCT DIMENSIONS	CM	50 x 50

## PERFORMANCE SPECIFICATION

DESCRIPTION	STANDARD USED	SPECIFICATION
WEAR CLASSIFICATION	-	CONTRACT
FLAMMABILITY	BS4790	PASS/LOW RADIUS OF CHAR
STROLL TEST	BS ISO 6356	< 2kV
STABILITY	DIN54318	MAX. CHANGE 0.25%
CASTOR CHAIR	BS EN 985	PASS (USE PROTECTIVE MATS UNDER CASTOR CHAIRS)
FASTNESS TO LIGHT	BS EN ISO 105	>5
FASTNESS TO WATER	BS EN ISO 105	4-5
FASTNESS TO SHAMPOO	BS 1006	5
FASTNESS TO RUBBING (WET)	BS EN ISO 105	4-5
FASTNESS TO RUBBING (DRY)	BS EN ISO 105	4-5



National  
Carpet  
Tiles

*When quality counts*

Telephone 01706 714455  
Fax 01706 714454  
[www.nationalcarpettiles.co.uk](http://www.nationalcarpettiles.co.uk)