## PRODUCT SPECIFICATION

DESCRIPTION	Standard Used	SPECIFICATION
Manufacturing Method	-	TUFTED
Machine Gauge	INCHES	1/10
PILE CONSTRUCTION	-	LOOP
PILE YARN COMPOSITION	-	IOO% POLYPROPYLENE
PRIMARY BACKING	GM./M2	NON WOVEN POLYESTER
PILE WEIGHT	GM./M2	550
Total Weight	GM./M2	4,300
PILE HEIGHT	ММ	5
TOTAL HEIGHT	ММ	7
STITCH DENSITY	Tufts/M2	189,120
PRODUCT DIMENSIONS	СМ	50 x 50

## PERFORMANCE SPECIFICATION

DESCRIPTION	STANDARD USED	SPECIFICATION
FLAMMABILITY	ISO 13501-1	CfLsI
CASTOR CHAIR	BS EN 985/A	Pass (USE PROTECTIVE MATS)
FASTNESS TO LIGHT	BS EN ISO 105	5 - 6
FASTNESS TO WATER	BS EN ISO 105	4 - 5

This product is covered by a 7 year wear warranty and a 7 year anti-static warranty. For further information or for copy of our full warranty, please contact our help desk

THE CONSTRUCTION OF THIS PRODUCT HAS BEEN ENGINEERED TO PROVIDE OPTIMUM PERFORMANCE IN HEAVY CONTRACT INSTALLATIONS SUCH AS AS SHOWROOMS, OFFICES, HOTEL BEDROOMS ETC. PLEASE CONTACT OUR HELP DESK FOR ADVICE ON SPECIFIC INSTALLATIONS



PILE DIRECTION - FOR BEST RESULTS, THIS PRODUCT SHOULD BE LAID CHEQUEBOARD

