

TITAN

PRODUCT SPECIFICATION


DESCRIPTION	STANDARD USED	SPECIFICATION
MANUFACTURING METHOD	-	TUFTED
MACHINE GAUGE	INCHES	1/10
PILE CONSTRUCTION	-	LOOP
PILE YARN COMPOSITION	-	100% SOLUTION DYED NYLON
PRIMARY BACKING	GM./M ²	NON WOVEN POLYESTER
SECONDARY BACKING	KG./M ²	3
PILE WEIGHT	GM./M ²	550
TOTAL WEIGHT	GM./M ²	4,390
PILE HEIGHT	MM	3.50
STITCH DENSITY	TUFTS/M ²	181,162
PRODUCT DIMENSIONS	CM	50 x 50

PERFORMANCE SPECIFICATION

DESCRIPTION	STANDARD USED	SPECIFICATION
WEAR CLASSIFICATION	EN 1307	CONTRACT CLASS 32
FLAMMABILITY	ISO 13501-1	CFLs1
STROLL TEST	BS ISO 6356	< 2kV
STABILITY	ISO 2551	< 0.2%
CASTOR CHAIR	BS EN 985/A	PASS (USE PROTECTIVE MATS UNDER CASTOR CHAIRS)
STATIC LOADING	BS4939	85% RECOVERY (24 HRS)
FASTNESS TO LIGHT	BS EN ISO 105	>6
FASTNESS TO WATER	BS EN ISO 105	5
FASTNESS TO SHAMPOO	BS 1006	5
FASTNESS TO RUBBING (WET)	BS EN ISO 105	5
FASTNESS TO RUBBING (DRY)	BS EN ISO 105	5

THIS PRODUCT IS COVERED BY A 10 YEAR WEAR WARRANTY AND A 10 YEAR ANTI-STATIC WARRANTY. FOR FURTHER INFORMATION OR FOR COPY OF OUR FULL WARRANTY, PLEASE CONTACT OUR HELP DESK

THE CONSTRUCTION OF THIS PRODUCT HAS BEEN ENGINEERED TO PROVIDE OPTIMUM PERFORMANCE IN HEAVY CONTRACT INSTALLATIONS SUCH AS AS SHOWROOMS, OFFICES, HOTEL BEDROOMS ETC. FOR BEST RESULTS, THIS PRODUCT SHOULD BE LAID CHEQUERBOARD. PLEASE CONTACT OUR HELP DESK FOR ADVICE ON SPECIFIC INSTALLATIONS



PILE DIRECTION - FOR BEST RESULTS, THIS PRODUCT SHOULD BE LAID CHEQUEBOARD



National
Carpet
Tiles

When quality counts

Telephone 01706 714455
Fax 01706 714454
www.nationalcarpettiles.co.uk