

SELECT

PRODUCT SPECIFICATION

DESCRIPTION	STANDARD USED	SPECIFICATION
MANUFACTURING METHOD	-	TUFTED
MACHINE GAUGE	INCHES	1/10
PILE CONSTRUCTION	-	LOOP
PILE YARN COMPOSITION	-	100% BCF POLYPROPYLENE
PRIMARY BACKING	GM./M2	90 NON WOVEN
SECONDARY BACKING	GM./M2	950 LATEX PRE COAT
BITUMEN PLUS NON WOVEN FLEECE	GM./M2	2,740
PILE WEIGHT	GM./M2	400
TOTAL WEIGHT	GM./M2	4,180
PILE HEIGHT	MM	3.50
STITCH RATE	ST PER 10CM	38
STITCH DENSITY	TUFTS/M2	150,000
PRODUCT DIMENSIONS	CM	50 x 50

PERFORMANCE SPECIFICATION

DESCRIPTION	STANDARD USED	SPECIFICATION
WEAR CLASSIFICATION	-	CONTRACT
FLAMMABILITY	BS4790	PASS/LOW RADIUS OF CHAR
STROLL TEST	BS ISO 6356	< 2kV
STABILITY	DIN54318	MAX. CHANGE 0.25%
CASTOR CHAIR	BS EN 985	PASS (USE PROTECTIVE MATS UNDER CASTOR CHAIRS)
STATIC LOADING	BS4939	85% RECOVERY (24 HRS)
FASTNESS TO LIGHT	BS EN ISO 105	>5
FASTNESS TO WATER	BS EN ISO 105	4-5
FASTNESS TO SHAMPOO	BS 1006	5
FASTNESS TO RUBBING (WET)	BS EN ISO 105	4-5
FASTNESS TO RUBBING (DRY)	BS EN ISO 105	4-5



National
Carpet
Tiles

When quality counts

Telephone 01706 714455
Fax 01706 714454
www.nationalcarpettiles.co.uk