UNIVERSE

PRODUCT SPECIFICATION

DESCRIPTION	Standard Used	SPECIFICATION
Manufacturing Method	-	Tufted
Machine Gauge	INCHES	1/10
PILE CONSTRUCTION	-	LOOP PILE
PILE YARN COMPOSITION	-	I 00% Solution Dyed Alto Chroma™ nylon
PRIMARY BACKING	GM./M2	I OO NON WOVEN
SECONDARY BACKING	GM./M2	BITUMEN WITH GLASS FIBRE
PILE WEIGHT	GM./M2	750
TOTAL WEIGHT	GM./M2	4,540
PILE HEIGHT	ММ	3.40
STITCH DENSITY	Tufts/M2	96,457
PRODUCT DIMENSIONS	СМ	50 x 50

PERFORMANCE SPECIFICATION

DESCRIPTION	Standard Used	Specification	
Wear Rating	BS EN 1307	CLASS 33	
FLAMMABILITY	ISO I 350 I -O I	BFL-S1	
Castor Chair	BS EN 985/A	> 2.4	

THIS PRODUCT IS COVERED BY A IO YEAR WEAR WARRANTY AND A IO YEAR ANTI-STATIC WARRANTY. FOR FURTHER INFORMATION OR FOR A COPY OF OUR FULL WARRANTY, PLEASE CONTACT OUR HELP DESK

THE CONSTRUCTION OF THIS PRODUCT HAS BEEN ENGINEERED TO PROVIDE OPTIMUM PERFORMANCE IN HEAVY CONTRACT INSTALLATIONS SUCH AS SHOWROOMS, OFFICES, HOTEL BEDROOMS ETC.

PLEASE CONTACT OUR HELP DESK FOR ADVICE ON SPECIFIC INSTALLATIONS

